

TECHNICAL DATA

SHARP 100 80V/80A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	SR6381
Model	SHARP 100
Type	80V/80A

MAINS DATA (50/60HZ)

Output Voltage [V]	80
Output Current [A]	80
Number of phases	3
Rated Voltage range [V]	380-415
Current at nominal voltage [A]	12.5
Recommended supply fuse [A]	16
Supply cable area	4x2,5 mm ²
Supply cable length [m]	3
Typical Supply Connector	CEE16
Output cable cross-section	25 mm ²

BATTERY CONNECTION

Output cable cross-section	25 mm ²
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	80

ELECTRIC DATA

Standby Power Consumption [W]	<10
Power Consumption [W]	8218
Apparent Power Consumption [VA]	8650

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	94

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	
Cabinet Type	S17
Certifications	CE
HMI	
HMI Language	
Reporting	No
Radio Communication	No
Charging Curve Set	
I/O-cards	
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]	14
Weight incl. cables [kg]	17
Outer Dimensions Height [mm]	417

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	243
Min Spacing Required	Se User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	20
Box Height [mm]	465
Box Width [mm]	365
Box Depth [mm]	525

CHARGING

Charging Ionic

Charging Standard

Charging Gel

Charging Li-Ion

Charging AGM

Moisture Resistance No

Dusty Environment No

Outdoor use No

Cold store No

Tropical No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.