

TECHNICAL DATA

MICROPOWER ST60 LI BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	
Model	Micropower ST60
Type	80V/60A
MAINS DATA (50/60HZ)	
Output Voltage [V]	80
Output Current [A]	60
Number of phases	3
Rated Voltage range [V]	380-440
Current at nominal voltage [A]	9,3
Recommended supply fuse [A]	10
Supply cable area	4x1,5 mm2
Supply cable length [m]	3
Typical Supply Connector	CEE16
Output cable cross-section	16 mm2
BATTERY CONNECTION	
Output cable cross-section	16 mm2
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	80
ELECTRIC DATA	
Standby Power Consumption [W]	<5
Power Consumption [W]	6101
Apparent Power Consumption [VA]	6422

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	95

PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A24
Certifications	CE
HMI	LED/Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Lithium CAN
I/O-cards	CAN/Detect
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h
8 Hours cap.ah/5h
10 Hours cap.ah/5h
12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]	9
Weight incl. cables [kg]	10
Outer Dimensions Height [mm]	338

Outer Dimensions Width [mm]	335
Outer Dimensions Depth [mm]	239
Min Spacing Required	See User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	13
Box Height [mm]	350
Box Width [mm]	380
Box Depth [mm]	530

CHARGING

Charging Ionic	
Charging Standard	
Charging Gel	
Charging Li-Ion	
Charging AGM	
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.