

## TECHNICAL DATA

# MICROPOWER SQ50 PB 36V/105A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

|             |                 |
|-------------|-----------------|
| Family      | Micropower SQ50 |
| DC Rating   | 36V/105A        |
| Part number | SN3436          |
| Model code  | 1AB64N2         |
| Part status | Released        |

### SUPPLY

|                                               |         |
|-----------------------------------------------|---------|
| Number of phases                              | 3       |
| Rated Voltage range [V]                       | 480     |
| Nominal Voltage [V]                           | 480     |
| Rated frequency [Hz]                          | 50-60   |
| Current at nominal voltage [A]                | 6,2     |
| Current at min rated voltage [A]              | 6,2     |
| Current at max rated voltage [A]              | 6,2     |
| Recommended supply fuse class                 | C       |
| Recommended RCCB class                        | B       |
| Supply cable area                             | 4xAWG14 |
| Supply cable length [m]                       | □2,5    |
| Typical Supply Connector                      | L16-20P |
| Standby Power Consumption [W]                 | <2,5    |
| Power Consumption [W]                         | 4876    |
| Apparent Power Consumption [VA]               | 5187    |
| Power Factor                                  | 0,94    |
| Leakage current [mA]                          | <3,5    |
| Efficiency (at rated power and no cables) [%] | 94      |

## OUTPUT DATA

|                                  |                         |
|----------------------------------|-------------------------|
| Reversed polarity protection     | Fuse                    |
| Short Circuit Protection         | Yes                     |
| Output Voltage [V]               | 36                      |
| Output Current [A]               | 105                     |
| Output cable cross-section       | #2 AWG                  |
| Output cable length [m]          | 3                       |
| Output cable terminals (in unit) | M6                      |
| Typical Output connector         | DIN160                  |
| Output fuse, rating [A/VDC]      | 125A/150VDC             |
| Output fuse type                 | Fast Semiconductor fuse |

## PROPERTIES

|                                                          |                     |
|----------------------------------------------------------|---------------------|
| Ingress protection                                       | IP21                |
| Ambient temperature range (at full output power) [deg C] | -5 to +40           |
| Ambient max temp (with reduced output power) [deg C]     | 50                  |
| Ambient storage and transport temperature [C]            | -40 to +80/1000h    |
| Maximum operating altitude [m]                           | 2000                |
| Maximum humidity, non-condensing [%rh]                   | 90                  |
| Cooling                                                  | Convection          |
| Cabinet Type                                             | A24                 |
| Certifications                                           | UL                  |
| Cloud connection                                         | No                  |
| User interface                                           | LED                 |
| Charging Curve Set                                       | 10-04,06,18 & 20-09 |
| I/O-cards                                                | Optional            |
| Reporting                                                | No                  |
| Radio communication                                      | No                  |

## CHARGER DIMENSIONS

|                          |             |
|--------------------------|-------------|
| Weight excl. cables [kg] | 8           |
| Charger dimensions [mm]  | 338x335x239 |

## SHIPPING DIMENSIONS

Box dimensions [mm]

350x380x530

Shipping Weight [kg]

14

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*