

TECHNICAL DATA

ACCESS 100 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	UA4557
Model	ACCESS 100
Type	48V/165A

MAINS DATA (50/60HZ)

Output Voltage [V]	48
Output Current [A]	165
Number of phases	3
Rated Voltage range [V]	600-600
Current at nominal voltage [A]	10,6
Recommended supply fuse [A]	16
Supply cable area	4xAWG14
Supply cable length [m]	3
Typical Supply Connector	Not included
Output cable cross-section	2xAWG1/0

BATTERY CONNECTION

Output cable cross-section	2xAWG1/0
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	User defined
Output Voltage [V]	48

ELECTRIC DATA

Standby Power Consumption [W]	< 10
Power Consumption [W]	10449
Apparent Power Consumption [VA]	10999

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	Negligible
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	92

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	A19
Certifications	UL
HMI	LED / Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Multiple
I/O-cards	Optional
CE	No
UL	No

CHARGING TIMES

6 Hours cap.ah/5h	947
8 Hours cap.ah/5h	1778
10 Hours cap.ah/5h	1834
12 Hours cap.ah/5h	2848

CHARGER DIMENSIONS

Weight excl. cables [kg]	
Weight incl. cables [kg]	
Outer Dimensions Height [mm]	571

Outer Dimensions Width [mm]	270
Outer Dimensions Depth [mm]	258
Min Spacing Required	300

SHIPPING DIMENSIONS

Shipping Weight [kg]	25
Box Height [mm]	440
Box Width [mm]	370
Box Depth [mm]	560

CHARGING

Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.