

TECHNICAL DATA

ACCESS 260 80V/260A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	ACCESS 260
DC Rating	80V/260A
Part number	AY6726
Model code	1AA8603
Part status	Released

SUPPLY

Number of phases	3
Rated Voltage range [V]	460-480
Nominal Voltage [V]	480
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	33,5
Current at min rated voltage [A]	35
Current at max rated voltage [A]	33,5
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4xAWG8
Supply cable length [m]	2.5
Typical Supply Connector	L16-50P, optional
Standby Power Consumption [W]	<10
Power Consumption [W]	26437
Apparent Power Consumption [VA]	27829
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	95

OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	80
Output Current [A]	260
Output cable cross-section	3/0 AWG
Output cable length [m]	3
Output cable terminals (in unit)	M10
Typical Output connector	DIN320
Output fuse, rating [A/VDC]	2x150A/150VDC
Output fuse type	Fast Semiconductor fuse

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A26
Certifications	UL
Cloud connection	Yes
User interface	
Charging Curve Set	Multiple
I/O-cards	
Reporting	Yes
Radio communication	Yes

CHARGER DIMENSIONS

Weight excl. cables [kg]	36
Charger dimensions [mm]	xx

SHIPPING DIMENSIONS

Box dimensions [mm]

565x325x890

Shipping Weight [kg]

50

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.