

TECHNICAL DATA

MIL DC-DC CONVERTER NON ISOLATED DC-DC CONVERTERS & CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|-------------|----------------------|
| Part number | 0060363MIL |
| Model | MIL DC-DC Converters |
| Type | 24-12VDC 30A |

MAINS DATA (50/60HZ)

| | |
|--------------------------------|----|
| Output Voltage [V] | 12 |
| Output Current [A] | |
| Number of phases | |
| Rated Voltage range [V] | |
| Current at nominal voltage [A] | |
| Recommended supply fuse [A] | |
| Supply cable area | |
| Supply cable length [m] | |
| Typical Supply Connector | |
| Output cable cross-section | |

BATTERY CONNECTION

| | |
|----------------------------------|----|
| Output cable cross-section | |
| Output cable terminals (in unit) | |
| Output cable length [m] | |
| Typical Output connector | |
| Output Voltage [V] | 12 |

PROPERTIES

| | |
|--|------|
| Ingress protection | IP67 |
| Ambient temperature range (at full output power) [deg C] | |

Ambient max temp (with reduced output power) [deg C]

Cooling

Short Circuit Protection

Wrong Polarity Protection

Cabinet Type

Certifications

HMI

HMI Language

Reporting

Radio Communication

Charging Curve Set

I/O-cards

CE

UL

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.