

TECHNICAL DATA

MICROPOWER SX17 LI 24V/60A UR BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	Micropower SX17
DC Rating	24V/60A
Part number	WM2340-A2
Model code	3AGD716
Part status	Released

SUPPLY

Number of phases	1
Rated Voltage range [V]	220-240
Nominal Voltage [V]	230
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	8.6
Current at min rated voltage [A]	15
Current at max rated voltage [A]	8.3
Recommended supply fuse class	C
Recommended RCCB class	A
Supply cable area	3xAWG14
Supply cable length [m]	2
Typical Supply Connector	Fixed NEMA 6-20P
Standby Power Consumption [W]	<5
Power Consumption [W]	1942,417582
Apparent Power Consumption [VA]	1982,058758
Power Factor	0.98
Leakage current [mA]	<3.5
Efficiency (at rated power and no cables) [%]	91

OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	24
Output Current [A]	60
Output cable cross-section	AWG2
Output cable length [m]	3
Output cable terminals (in unit)	M6
Typical Output connector	DIN80
Output fuse, rating [A/VDC]	160A/150VDC
Output fuse type	Fast Semiconductor fuse

PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	55
Ambient storage and transport temperature [C]	-25 to +60/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A51
Certifications	UR
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Litium CAN
I/O-cards	Basic option are integrated
Reporting	Yes
Radio communication	Yes

CHARGER DIMENSIONS

Weight excl. cables [kg]	6
Charger dimensions [mm]	455x220x103

SHIPPING DIMENSIONS

Box dimensions [mm]	165x265x595
Shipping Weight [kg]	9.4

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.