MICROPOWER GROUP™
POWERFUL SOLUTIONS PARTNER

TECHNICAL DATA

MICROPOWER SL190 PB 120V/180A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	DB7589-3073
Model	SL190
Type	90V/180A
MAINS DATA (50/60HZ)	
Output Voltage [V]	90
Output Current [A]	180
Number of phases	3
Rated Voltage range [V]	380-440
Current at nominal voltage [A]	30.9
Recommended supply fuse [A]	32
Supply cable area	4x6 mm2
Supply cable length [m]	□2.5
Typical Supply Connector	CEE32
Output cable cross-section	70 mm2
BATTERY CONNECTION	
Output cable cross-section	70 mm2
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN320
Output Voltage [V]	90
ELECTRIC DATA	
Standby Power Consumption [W]	<3.5
Power Consumption [W]	20458
Apparent Power Consumption [VA]	21377

Power Factor	0.96
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	96

PROPERTIES

Ingress protection	IP21
Operation Temperature [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	
Cabinet Type	B2
Certifications	CE
HMI	
HMI Language	
Reporting	No
Radio Communication	No
Charging Curve Set	
I/O-cards	
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h	
8 Hours cap.ah/5h	
10 Hours cap.ah/5h	
12 Hours cap.ah/5h	

CHARGER DIMENSIONS

Weight excl. cables [kg]	42
Weight incl. cables [kg]	49
Outer Dimensions Height [mm]	410

Outer Dimensions Width [mm]	533
Outer Dimensions Depth [mm]	515
Min Spacing Required	See User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	63
Box Height [mm]	560
Box Width [mm]	800
Box Depth [mm]	600

CHARGING

Charging Ionic	
Charging Standard	
Charging Gel	
Charging Li-Ion	
Charging AGM	
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.

Micropower Group
Gulhallavägen 20
SE-352 50 Växjö
Sweden

Phone: +46 (0) 470-72 74 00
sales@micropower.se
www.micropower-group.se