

TECHNICAL DATA

MICROPOWER SL250 LI 90V/260A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	EB6729-3073
Model	SL250
Type	90V/260A

MAINS DATA (50/60HZ)

Output Voltage [V]	90
Output Current [A]	260
Number of phases	3
Rated Voltage range [V]	380-440
Current at nominal voltage [A]	39.6
Recommended supply fuse [A]	50
Supply cable area	4x10 mm ²
Supply cable length [m]	12.5
Typical Supply Connector	CEE63
Output cable cross-section	95 mm ²

BATTERY CONNECTION

Output cable cross-section	95 mm ²
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	Cobra
Output Voltage [V]	90

ELECTRIC DATA

Standby Power Consumption [W]	<3.5
Power Consumption [W]	26223
Apparent Power Consumption [VA]	27401

Power Factor	0.96
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	96

PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	
Cabinet Type	B2
Certifications	CE
HMI	
HMI Language	
Reporting	No
Radio Communication	No
Charging Curve Set	
I/O-cards	
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h
8 Hours cap.ah/5h
10 Hours cap.ah/5h
12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]	42
Weight incl. cables [kg]	50
Outer Dimensions Height [mm]	410

Outer Dimensions Width [mm]	533
Outer Dimensions Depth [mm]	515
Min Spacing Required	See User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	64
Box Height [mm]	560
Box Width [mm]	800
Box Depth [mm]	600

CHARGING

Charging Ionic	
Charging Standard	
Charging Gel	
Charging Li-Ion	
Charging AGM	
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.