

TECHNICAL DATA

ACCESS 30 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	AB3320
Model	ACCESS 30
Type	36V/53A

MAINS DATA (50/60HZ)

Output Voltage [V]	36
Output Current [A]	53
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	10
Recommended supply fuse [A]	10
Supply cable area	3x1,5
Supply cable length [m]	2,5
Typical Supply Connector	16A Schuko
Output cable cross-section	2x16

BATTERY CONNECTION

Output cable cross-section	2x16
Output cable terminals (in unit)	-
Output cable length [m]	3
Typical Output connector	User defined
Output Voltage [V]	36

ELECTRIC DATA

Standby Power Consumption [W]	<5
Power Consumption [W]	2325
Apparent Power Consumption [VA]	2349

Power Factor	0,99
Inrush current, do not tripp fuse of class [A]	<30
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	92

PROPERTIES

Ingress protection	IP54 (IP66 optional)
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	A11
Certifications	CE
HMI	LED
HMI Language	-
Reporting	Yes
Radio Communication	No
Charging Curve Set	Multiple
I/O-cards	No
CE	No
UL	No

CHARGING TIMES

6 Hours cap.ah/5h	311
8 Hours cap.ah/5h	450
10 Hours cap.ah/5h	589
12 Hours cap.ah/5h	729

CHARGER DIMENSIONS

Weight excl. cables [kg]	
Weight incl. cables [kg]	
Outer Dimensions Height [mm]	407

Outer Dimensions Width [mm]	235
Outer Dimensions Depth [mm]	78
Min Spacing Required	100

SHIPPING DIMENSIONS

Shipping Weight [kg]	8
Box Height [mm]	600
Box Width [mm]	265
Box Depth [mm]	165

CHARGING

Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.