

## TECHNICAL DATA

# ACCESS 50 24V/130A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	AP2483
Model	ACCESS 50
Type	24V/130A

#### MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	130
Number of phases	3
Rated Voltage range [V]	200-240
Current at nominal voltage [A]	12.7
Recommended supply fuse [A]	16
Supply cable area	4x2,5 mm <sup>2</sup>
Supply cable length [m]	3
Typical Supply Connector	CEE16
Output cable cross-section	50 mm <sup>2</sup>

#### BATTERY CONNECTION

Output cable cross-section	50 mm <sup>2</sup>
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN160
Output Voltage [V]	24

#### ELECTRIC DATA

Standby Power Consumption [W]	< 5
Power Consumption [W]	4189
Apparent Power Consumption [VA]	4409

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	91

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A16
Certifications	CE
HMI	LED/Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Multiple
I/O-cards	Optional
CE	Yes
UL	No

## CHARGING TIMES

6 Hours cap.ah/5h	746
8 Hours cap.ah/5h	1083
10 Hours cap.ah/5h	1446
12 Hours cap.ah/5h	1992

## CHARGER DIMENSIONS

Weight excl. cables [kg]	7
Weight incl. cables [kg]	11
Outer Dimensions Height [mm]	387

Outer Dimensions Width [mm]	266
Outer Dimensions Depth [mm]	152
Min Spacing Required	Se User Manual

## SHIPPING DIMENSIONS

Shipping Weight [kg]	12
Box Height [mm]	260
Box Width [mm]	325
Box Depth [mm]	550

## CHARGING

Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.*