

## **TECHNICAL DATA**

## LION 100 80V/80A BATTERY CHARGERS

## STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	L\$6383
Model	LION 100
Туре	80V/80A
MAINS DATA (50/60HZ)	
Output Voltage [V]	80
Output Current [A]	80
Number of phases	3
Rated Voltage range [V]	208-240
Current at nominal voltage [A]	24.3
Recommended supply fuse [A]	25
Supply cable area	4x4 mm2
Supply cable length [m]	3
Typical Supply Connector	CEE32
Output cable cross-section	25 mm2
BATTERY CONNECTION	
Output cable cross-section	25 mm2
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	80
ELECTRIC DATA	
Standby Power Consumption [W]	< 10
Power Consumption [W]	8306
Apparent Power Consumption [VA]	8743

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	В
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	93
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A18
Certifications	CE
НМІ	LED / Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	No
Charging Curve Set	N/A
I/O-cards	Yes
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	
8 Hours cap.ah/5h	
10 Hours cap.ah/5h	
12 Hours cap.ah/5h	
CHARGER DIMENSIONS	
Weight excl. cables [kg]	16
Weight incl. cables [kg]	19
Outer Dimensions Height [mm]	529

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	244
Min Spacing Required	Se User Manual
SHIPPING DIMENSIONS	
Shipping Weight [kg]	22
Box Height [mm]	650
Box Width [mm]	370
Box Depth [mm]	440
CHARGING	
Charging Ionic	0
Charging Standard	0
Charging Gel	0
Charging Li-Ion	0
Charging AGM	0
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.