

TECHNICAL DATA

LION 100 80V/100A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	LION 100
DC Rating	80V/100A
Part number	LR6421
Model code	1AA7505
Part status	Released

SUPPLY

Number of phases	3
Rated Voltage range [V]	380-415
Nominal Voltage [V]	400
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	15.6
Current at min rated voltage [A]	16.4
Current at max rated voltage [A]	15.1
Recommended supply fuse class	C
Recommended RCCB class	A
Supply cable area	4x2,5 mm ²
Supply cable length [m]	3
Typical Supply Connector	CEE16
Standby Power Consumption [W]	< 10
Power Consumption [W]	10266
Apparent Power Consumption [VA]	10806
Power Factor	0.95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	94

OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	80
Output Current [A]	100
Output cable cross-section	35 mm ²
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN160
Output fuse, rating [A/VDC]	150A/150VDC
Output fuse type	Fast Semiconductor fuse

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A17
Certifications	CE
Cloud connection	Yes
User interface	LED / Display
Charging Curve Set	Litium Alg or CAN
I/O-cards	CAN/Detect
Reporting	Yes
Radio communication	Yes

CHARGER DIMENSIONS

Weight excl. cables [kg]	14
Charger dimensions [mm]	417x256x243

SHIPPING DIMENSIONS

Box dimensions [mm]	465x365x525
Shipping Weight [kg]	20

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.