

TECHNICAL DATA

LION 100 36V/220A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	LT3666
Model	LION 100
Type	36V/220A

MAINS DATA (50/60HZ)

Output Voltage [V]	36
Output Current [A]	220
Number of phases	3
Rated Voltage range [V]	-
Current at nominal voltage [A]	13.3
Recommended supply fuse [A]	16
Supply cable area	4xAWG12
Supply cable length [m]	3
Typical Supply Connector	L16-20P
Output cable cross-section	2/0 AWG

BATTERY CONNECTION

Output cable cross-section	2/0 AWG
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN320
Output Voltage [V]	36

ELECTRIC DATA

Standby Power Consumption [W]	< 10
Power Consumption [W]	10488
Apparent Power Consumption [VA]	11040

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	92

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A19
Certifications	UL
HMI	LED / Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	No
Charging Curve Set	N/A
I/O-cards	Yes
CE	No
UL	Yes

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]	19
Weight incl. cables [kg]	26
Outer Dimensions Height [mm]	571

Outer Dimensions Width [mm]	270
Outer Dimensions Depth [mm]	258
Min Spacing Required	Se User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	28
Box Height [mm]	535
Box Width [mm]	315
Box Depth [mm]	850

CHARGING

Charging Ionic	0
Charging Standard	0
Charging Gel	0
Charging Li-Ion	0
Charging AGM	0
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.