

TECHNICAL DATA

LION 30 24V/100A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	LC2420
Model	LION 30
Type	24V/100A

MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	100
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	13,9
Recommended supply fuse [A]	16
Supply cable area	3x1,5 mm ²
Supply cable length [m]	2,5
Typical Supply Connector	CEE17
Output cable cross-section	25 mm ²

BATTERY CONNECTION

Output cable cross-section	25 mm ²
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN160
Output Voltage [V]	24

ELECTRIC DATA

Standby Power Consumption [W]	<5
Power Consumption [W]	3172
Apparent Power Consumption [VA]	3204

Power Factor	0,99
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	93

PROPERTIES

Ingress protection	IP54 (IP66 optional)
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A12
Certifications	CE
HMI	LED
HMI Language	-
Reporting	Yes
Radio Communication	No
Charging Curve Set	N/A
I/O-cards	No
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]	7
Weight incl. cables [kg]	9
Outer Dimensions Height [mm]	408

Outer Dimensions Width [mm]	235
Outer Dimensions Depth [mm]	78
Min Spacing Required	See User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	11
Box Height [mm]	165
Box Width [mm]	265
Box Depth [mm]	600

CHARGING

Charging Ionic	0
Charging Standard	0
Charging Gel	0
Charging Li-Ion	0
Charging AGM	0
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.