

TECHNICAL DATA

LION 30 24V/100A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD	
Part number	LC2420
Model	LION 30
Туре	24V/100A
MAINS DATA (50/60HZ)	
Output Voltage [V]	24
Output Current [A]	100
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	13,9
Recommended supply fuse [A]	16
Supply cable area	3x1,5 mm2
Supply cable length [m]	2,5
Typical Supply Connector	CEE17
Output cable cross-section	25 mm2
BATTERY CONNECTION	
Output cable cross-section	25 mm2
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN160
Output Voltage [V]	24
ELECTRIC DATA	
Standby Power Consumption [W]	<5
Power Consumption [W]	3172
Apparent Power Consumption [VA]	3204

Printout date: 2025-12-13

Power Factor	0,99
Inrush current, do not tripp fuse of class [A]	В
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	93
PROPERTIES PROPERTIES	
Ingress protection	IP54 (IP66 optional)
Ambient temperature range (at full output power) [deg C]	-5 to +40
	50
Ambient max temp (with reduced output power) [deg C]	
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A12
Certifications	CE
НМІ	LED
HMI Language	-
Reporting	Yes
Radio Communication	No
Charging Curve Set	N/A
I/O-cards	No
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	
8 Hours cap.ah/5h	
10 Hours cap.ah/5h	
12 Hours cap.ah/5h	
CHARGER DIMENSIONS	
Weight excl. cables [kg]	7
Weight incl. cables [kg]	9
Outer Dimensions Height [mm]	408

Outer Dimensions Width [mm]	235
Outer Dimensions Depth [mm]	78
Min Spacing Required	See User Manual
SHIPPING DIMENSIONS	
Shipping Weight [kg]	11
Box Height [mm]	165
Box Width [mm]	265
Box Depth [mm]	600
CHARGING	
Charging Ionic	0
Charging Standard	0
Charging Gel	0
Charging Li-lon	0
Charging AGM	0
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No