

TECHNICAL DATA

LION 30 48V/20A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	LG4240
Model	LION 30
Type	48V/20A

MAINS DATA (50/60HZ)

Output Voltage [V]	48
Output Current [A]	20
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	5.5
Recommended supply fuse [A]	10
Supply cable area	3x1,0 mm ²
Supply cable length [m]	2,5
Typical Supply Connector	10A Schuko
Output cable cross-section	10 mm ²

BATTERY CONNECTION

Output cable cross-section	10 mm ²
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	48

ELECTRIC DATA

Standby Power Consumption [W]	<5
Power Consumption [W]	1259
Apparent Power Consumption [VA]	1272

Power Factor	0.99
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	92

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Electronic & FUSE
Cabinet Type	A27
Certifications	CE
HMI	LED/Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	No
Charging Curve Set	Multiple
I/O-cards	CAN I/O Included
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]	5
Weight incl. cables [kg]	6
Outer Dimensions Height [mm]	417

Outer Dimensions Width [mm]	255
Outer Dimensions Depth [mm]	84
Min Spacing Required	Se User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	7
Box Height [mm]	185
Box Width [mm]	320
Box Depth [mm]	610

CHARGING

Charging Ionic	0
Charging Standard	0
Charging Gel	0
Charging Li-Ion	0
Charging AGM	0
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.