

TECHNICAL DATA

SHARP 100 36V/150A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	SS3523
Model	SHARP 100
Туре	36V/150A
MAINS DATA (50/60HZ)	
Output Voltage [V]	36
Output Current [A]	150
Number of phases	3
Rated Voltage range [V]	208-240
Current at nominal voltage [A]	21.1
Recommended supply fuse [A]	25
Supply cable area	4x4 mm2
Supply cable length [m]	3
Typical Supply Connector	CEE32
Output cable cross-section	50 mm2
BATTERY CONNECTION	
Output cable cross-section	50 mm2
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN160
Output Voltage [V]	36
ELECTRIC DATA	
Standby Power Consumption [W]	<10
Power Consumption [W]	7220
Apparent Power Consumption [VA]	7600

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	В
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	91
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	S18
Certifications	CE
НМІ	LED
HMI Language	
Reporting	No
Radio Communication	No
Charging Curve Set	10-04,06,18 & 20-09
I/O-cards	No
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	861
8 Hours cap.ah/5h	1250
10 Hours cap.ah/5h	1668
12 Hours cap.ah/5h	2002
CHARGER DIMENSIONS	
Weight excl. cables [kg]	16
Weight incl. cables [kg]	20
Outer Dimensions Height [mm]	529

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	243
Min Spacing Required	Se User Manual
SHIPPING DIMENSIONS	
Shipping Weight [kg]	23
Box Height [mm]	650
Box Width [mm]	370
Box Depth [mm]	440
CHARGING	
Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Standard Charging Gel	LK10-06 Standard Curve LK20-09
Charging Gel	LK20-09
Charging Gel Charging Li-Ion	LK20-09 0
Charging Gel Charging Li-Ion Charging AGM	LK20-09 0 LK20-09
Charging Gel Charging Li-Ion Charging AGM Moisture Resistance	LK20-09 0 LK20-09 No
Charging Gel Charging Li-Ion Charging AGM Moisture Resistance Dusty Environment	LK20-09 0 LK20-09 No No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.