

## TECHNICAL DATA

# SHARP 100 80V/60A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

|             |           |
|-------------|-----------|
| Family      | SHARP 100 |
| DC Rating   | 80V/60A   |
| Part number | SS6343    |
| Model code  | 1AB7718   |
| Part status | Released  |

### SUPPLY

|   |                     |
|---|---------------------|
| Number of phases                              | 3                   |
| Rated Voltage range [V]                       | 208-240             |
| Nominal Voltage [V]                           | 208                 |
| Rated frequency [Hz]                          | 50-60               |
| Current at nominal voltage [A]                | 18,2                |
| Current at min rated voltage [A]              | 18,2                |
| Current at max rated voltage [A]              | 15,8                |
| Recommended supply fuse class                 | C                   |
| Recommended RCCB class                        | B                   |
| Supply cable area                             | 4x4 mm <sup>2</sup> |
| Supply cable length [m]                       | □2.5                |
| Typical Supply Connector                      | GEE32               |
| Standby Power Consumption [W]                 | <10                 |
| Power Consumption [W]                         | 6236                |
| Apparent Power Consumption [VA]               | 6564                |
| Power Factor                                  | 0,95                |
| Leakage current [mA]                          | <3,5                |
| Efficiency (at rated power and no cables) [%] | 93                  |

## OUTPUT DATA

|                                  |                         |
|----------------------------------|-------------------------|
| Reversed polarity protection     | Fuse                    |
| Short Circuit Protection         | Yes                     |
| Output Voltage [V]               | 80                      |
| Output Current [A]               | 60                      |
| Output cable cross-section       | 16 mm <sup>2</sup>      |
| Output cable length [m]          | 3                       |
| Output cable terminals (in unit) | M8                      |
| Typical Output connector         | DIN80                   |
| Output fuse, rating [A/VDC]      | 80A/150VDC              |
| Output fuse type                 | Fast Semiconductor fuse |

## PROPERTIES

|  |                     |
|--|---------------------|
| Ingress protection                                       | IP20                |
| Ambient temperature range (at full output power) [deg C] | -5 to +40           |
| Ambient max temp (with reduced output power) [deg C]     | 50                  |
| Ambient storage and transport temperature [C]            | -40 to +80/1000h    |
| Maximum operating altitude [m]                           | 2000                |
| Maximum humidity, non-condensing [%rh]                   | 90                  |
| Cooling  | Convection          |
| Cabinet Type   | S18                 |
| Certifications   | CE                  |
| Cloud connection   | No                  |
| User interface   | LED                 |
| Charging Curve Set                                       | 10-04,06,18 & 20-09 |
| I/O-cards  | No                  |
| Reporting  | No                  |
| Radio communication                                      | No                  |

## CHARGER DIMENSIONS

|                          |             |
|--------------------------|-------------|
| Weight excl. cables [kg] | 16          |
| Charger dimensions [mm]  | 529x256x243 |

## SHIPPING DIMENSIONS

|                      |             |
|----------------------|-------------|
| Box dimensions [mm]  | 650x370x440 |
| Shipping Weight [kg] | 21          |

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*