

## TECHNICAL DATA

# SHARP 100 BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	SS999991
Model	SHARP 100
Type	24V/170A

#### MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	170
Number of phases	3
Rated Voltage range [V]	480-480
Current at nominal voltage [A]	7
Recommended supply fuse [A]	10
Supply cable area	4xAWG14
Supply cable length [m]	3
Typical Supply Connector	Not included
Output cable cross-section	2xAWG1/0

#### BATTERY CONNECTION

Output cable cross-section	2xAWG1/0
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	User defined
Output Voltage [V]	24

#### ELECTRIC DATA

Standby Power Consumption [W]	<10
Power Consumption [W]	5507
Apparent Power Consumption [VA]	5797

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	Negligible
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	91

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	S18
Certifications	
HMI	LED
HMI Language	-
Reporting	No
Radio Communication	No
Charging Curve Set	10-04,06,18 & 20-09
I/O-cards	No
CE	No
UL	Yes

## CHARGING TIMES

6 Hours cap.ah/5h	976
8 Hours cap.ah/5h	1415
10 Hours cap.ah/5h	1888
12 Hours cap.ah/5h	2266

## CHARGER DIMENSIONS

Weight excl. cables [kg]	
Weight incl. cables [kg]	
Outer Dimensions Height [mm]	529

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	243
Min Spacing Required	300

## SHIPPING DIMENSIONS

Shipping Weight [kg]	22
Box Height [mm]	440
Box Width [mm]	370
Box Depth [mm]	650

## CHARGING

Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.*