

TECHNICAL DATA

SHARP 20 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|-------------|----------|
| Part number | 924231 |
| Model | SHARP 20 |
| Type | 24V/45A |

MAINS DATA (50/60HZ)

| | |
|--------------------------------|------------|
| Output Voltage [V] | 24 |
| Output Current [A] | 45 |
| Number of phases | 1 |
| Rated Voltage range [V] | 220-240 |
| Current at nominal voltage [A] | 6,5 |
| Recommended supply fuse [A] | 10 |
| Supply cable area | 3x1,5 |
| Supply cable length [m] | 2,5 |
| Typical Supply Connector | 10A Schuko |
| Output cable cross-section | 2x10 |

BATTERY CONNECTION

| | |
|----------------------------------|--------------|
| Output cable cross-section | 2x10 |
| Output cable terminals (in unit) | M6 |
| Output cable length [m] | 2 |
| Typical Output connector | User defined |
| Output Voltage [V] | 24 |

ELECTRIC DATA

| | |
|---------------------------------|------|
| Standby Power Consumption [W] | <5 |
| Power Consumption [W] | 1488 |
| Apparent Power Consumption [VA] | 1503 |

| | |
|--|------------|
| Power Factor | 0,99 |
| Inrush current, do not tripp fuse of class [A] | Negligible |
| Output Ripple | <1 |
| Efficiency (at rated power and no cables) [%] | 89 |

PROPERTIES

| | |
|--|------------------|
| Ingress protection | IP20 |
| Ambient temperature range (at full output power) [deg C] | -5 to +40 |
| Ambient max temp (with reduced output power) [deg C] | 50 |
| Cooling | Fan |
| Short Circuit Protection | 1 |
| Wrong Polarity Protection | Electronic |
| Cabinet Type | P6 |
| Certifications | |
| HMI | LED |
| HMI Language | - |
| Reporting | No |
| Radio Communication | No |
| Charging Curve Set | 10-04,06 & 20-09 |
| I/O-cards | No |
| CE | Yes |
| UL | No |

CHARGING TIMES

| | |
|--------------------|-----|
| 6 Hours cap.ah/5h | 229 |
| 8 Hours cap.ah/5h | 345 |
| 10 Hours cap.ah/5h | 471 |
| 12 Hours cap.ah/5h | 598 |

CHARGER DIMENSIONS

| | |
|------------------------------|-----|
| Weight excl. cables [kg] | |
| Weight incl. cables [kg] | |
| Outer Dimensions Height [mm] | 295 |

| | |
|-----------------------------|-----|
| Outer Dimensions Width [mm] | 138 |
| Outer Dimensions Depth [mm] | 89 |
| Min Spacing Required | 150 |

SHIPPING DIMENSIONS

| | |
|----------------------|-----|
| Shipping Weight [kg] | 3 |
| Box Height [mm] | 390 |
| Box Width [mm] | 250 |
| Box Depth [mm] | 140 |

CHARGING

| | |
|---------------------|---|
| Charging Ionic | LK10-04 Chemical Acid Circulation (Ionic) |
| Charging Standard | LK10-06 Standard Curve |
| Charging Gel | LK20-09 |
| Charging Li-Ion | 0 |
| Charging AGM | LK20-09 |
| Moisture Resistance | No |
| Dusty Environment | No |
| Outdoor use | No |
| Cold store | No |
| Tropical | No |

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.