

TECHNICAL DATA

ACCESS 100 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	AS2621
Model	ACCESS 100
Type	24V/200A

MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	200
Number of phases	3
Rated Voltage range [V]	380-415
Current at nominal voltage [A]	9,8
Recommended supply fuse [A]	10
Supply cable area	4x1,5
Supply cable length [m]	3,0
Typical Supply Connector	CEE16
Output cable cross-section	2x70

BATTERY CONNECTION

Output cable cross-section	2x70
Output cable terminals (in unit)	M8
Output cable length [m]	3,0
Typical Output connector	User defined
Output Voltage [V]	24

ELECTRIC DATA

Standby Power Consumption [W]	<10
Power Consumption [W]	6462
Apparent Power Consumption [VA]	6802

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	Neglible
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	91

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	A18
Certifications	CE
HMI	LED/Display
HMI Language	SC/ EN / DE / ES / PT
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Multiple
I/O-cards	Optional
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h	
8 Hours cap.ah/5h	1665
10 Hours cap.ah/5h	2221
12 Hours cap.ah/5h	2665

CHARGER DIMENSIONS

Weight excl. cables [kg]	16.1
Weight incl. cables [kg]	23.2
Outer Dimensions Height [mm]	529

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	243
Min Spacing Required	300

SHIPPING DIMENSIONS

Shipping Weight [kg]	25.6
Box Height [mm]	440
Box Width [mm]	370
Box Depth [mm]	650

CHARGING

Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.