

TECHNICAL DATA

MICROPOWER SC14 LI-CAN 24V/50A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWE	R STANDARD
Part number	VJ2320
Model	Micropower SC14-LI-CAN
Туре	24V/50A
MAINS DATA (50/60HZ)	
Output Voltage [V]	24
Output Current [A]	50
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	7,2
Recommended supply fuse [A]	10
Supply cable area	3x1,0 mm2
Supply cable length [m]	2,3
Typical Supply Connector	IEC C14/CEE17
Output cable cross-section	16 mm2
BATTERY CONNECTION	
Output cable cross-section	16 mm2
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	24
ELECTRIC DATA	
Standby Power Consumption [W]	<5
Power Consumption [W]	1613
Apparent Power Consumption [VA]	1646

Printout date: 2025-09-23

Power Factor	0,98
Inrush current, do not tripp fuse of class [A]	В
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	91
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	55
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A50
Certifications	CE
HMI	LED
HMI Language	-
Reporting	Yes
Radio Communication	No
Charging Curve Set	BMS contol
I/O-cards	No
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	285
8 Hours cap.ah/5h	415
10 Hours cap.ah/5h	555
12 Hours cap.ah/5h	
CHARGER DIMENSIONS	
Weight excl. cables [kg]	2
Weight incl. cables [kg]	4
Outer Dimensions Height [mm]	333

Outer Dimensions Width [mm]	150
Outer Dimensions Depth [mm]	103
Min Spacing Required	See User Manual
SHIPPING DIMENSIONS	
Shipping Weight [kg]	5
Box Height [mm]	135
Box Width [mm]	290
Box Depth [mm]	390
CHARGING	
Charging Ionic	-
Charging Standard	-
Charging Gel	-
Charging Li-lon	CAN bus, external BMS
Charging AGM	-
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No