

TECHNICAL DATA

ACCESS 200 24V/300A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	ACCESS 200
DC Rating	24V/300A
Part number	AU2763
Model code	1AA8501
Part status	Released

SUPPLY

Number of phases	3
Rated Voltage range [V]	208-240
Nominal Voltage [V]	208
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	28,7
Current at min rated voltage [A]	28,7
Current at max rated voltage [A]	24,8
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4x6 mm ²
Supply cable length [m]	12,5
Typical Supply Connector	CEE32
Standby Power Consumption [W]	<15
Power Consumption [W]	9800
Apparent Power Consumption [VA]	10316
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	90

OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	24
Output Current [A]	300
Output cable cross-section	4/0 AWG
Output cable length [m]	3
Output cable terminals (in unit)	M10
Typical Output connector	DIN320
Output fuse, rating [A/VDC]	2x200A/150VDC
Output fuse type	Fast Semiconductor fuse

PROPERTIES

Ingress protection	IP20
Operation Temperature [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%]	90
Cooling	Fan
Cabinet Type	A22
Certifications	CE
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Multiple Lead
I/O-cards	Optional
Reporting	Yes
Radio communication	Yes

CHARGER DIMENSIONS

Weight excl. cables [kg]	34
Charger dimensions [mm]	659x256x459

SHIPPING DIMENSIONS

Box dimensions [mm]	435x370x690
---------------------	-------------

Shipping Weight [kg]	47
----------------------	----

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.