

## TECHNICAL DATA

# MICROPOWER SL250 PB 80V/260A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

|             |             |
|-------------|-------------|
| Family      | SL250       |
| DC Rating   | 80V/260A    |
| Part number | DB6726-B3/0 |
| Model code  | 1A5B2AM     |
| Part status | Released    |

### SUPPLY

|                                               |         |
|-----------------------------------------------|---------|
| Number of phases                              | 3       |
| Rated Voltage range [V]                       | 480     |
| Nominal Voltage [V]                           | 480     |
| Rated frequency [Hz]                          | 50-60   |
| Current at nominal voltage [A]                | 32,8    |
| Current at min rated voltage [A]              | 32,8    |
| Current at max rated voltage [A]              | 32,8    |
| Recommended supply fuse class                 | C       |
| Recommended RCCB class                        | B       |
| Supply cable area                             | 4xAWG8  |
| Supply cable length [m]                       | 12.5    |
| Typical Supply Connector                      | L16-50P |
| Standby Power Consumption [W]                 | <3,5    |
| Power Consumption [W]                         | 26080   |
| Apparent Power Consumption [VA]               | 27252   |
| Power Factor                                  | 0,96    |
| Leakage current [mA]                          | <3,5    |
| Efficiency (at rated power and no cables) [%] | 96      |

## OUTPUT DATA

|                                  |                         |
|----------------------------------|-------------------------|
| Reversed polarity protection     | Fuse                    |
| Short Circuit Protection         | Yes                     |
| Output Voltage [V]               | 80                      |
| Output Current [A]               | 260                     |
| Output cable cross-section       | 3/0 AWG                 |
| Output cable length [m]          | 3                       |
| Output cable terminals (in unit) | M8                      |
| Typical Output connector         | DIN320                  |
| Output fuse, rating [A/VDC]      | 2x150A/150VDC           |
| Output fuse type                 | Fast Semiconductor fuse |

## PROPERTIES

|                                                      |                   |
|------------------------------------------------------|-------------------|
| Ingress protection                                   | IP21              |
| Operation Temperature [deg C]                        | -5 to +40         |
| Ambient max temp (with reduced output power) [deg C] | 50                |
| Ambient storage and transport temperature [C]        | -40 to +80/1000h  |
| Maximum operating altitude [m]                       | 2000              |
| Maximum humidity, non-condensing [%]                 | 90                |
| Cooling                                              | Convection        |
| Cabinet Type                                         | B2                |
| Certifications                                       | UL                |
| Cloud connection                                     | Yes               |
| User interface                                       | LED/Display       |
| Charging Curve Set                                   | Multiple Lead     |
| I/O-cards                                            | Remote Start/Stop |
| Reporting                                            | Yes               |
| Radio communication                                  | Yes               |

## CHARGER DIMENSIONS

|                          |             |
|--------------------------|-------------|
| Weight excl. cables [kg] | 42          |
| Charger dimensions [mm]  | 410x533x515 |

# SHIPPING DIMENSIONS

|                      |             |
|----------------------|-------------|
| Box dimensions [mm]  | 560x800x600 |
| Shipping Weight [kg] | 70          |

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*