

TECHNICAL DATA

RC9 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	RC9
DC Rating	24V/30A
Part number	RD2271-C2
Model code	2A1F910
Part status	Released

SUPPLY

Number of phases	1
Rated Voltage range [V]	100-240
Nominal Voltage [V]	120/230
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	7,0/4,1
Current at min rated voltage [A]	8,4
Current at max rated voltage [A]	3,9
Recommended supply fuse class	C
Recommended RCCB class	A
Supply cable area	-
Supply cable length [m]	-
Typical Supply Connector	IEC 60320 Type C16, IP67
Standby Power Consumption [W]	<3
Power Consumption [W]	938
Apparent Power Consumption [VA]	957
Power Factor	0,98
Leakage current [mA]	<1
Efficiency (at rated power and no cables) [%]	96

OUTPUT DATA

Reversed polarity protection	YES
Short Circuit Protection	Yes
Output Voltage [V]	24
Output Current [A]	30
Output cable cross-section	-
Output cable length [m]	-
Output cable terminals (in unit)	M6 & M8
Typical Output connector	-
Output fuse, rating [A/VDC]	60A/72VDC
Output fuse type	non-replaceable, medium acting

PROPERTIES

Ingress protection	IP67
Operation Temperature [deg C]	-35 to +40
Ambient max temp (with reduced output power) [deg C]	+70
Ambient storage and transport temperature [C]	-40 to +85/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%]	95
Cooling	Convection
Cabinet Type	R2
Certifications	CE/UL
Cloud connection	No
User interface	LED
Charging Curve Set	Multiple Lead/Lilon/CAN
I/O-cards	No
Reporting	No
Radio communication	No

CHARGER DIMENSIONS

Weight excl. cables [kg]	2
Charger dimensions [mm]	122x73x278

SHIPPING DIMENSIONS

Box dimensions [mm]

-X-X-

Shipping Weight [kg]

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.