MICROPOWER GROUP™
POWERFUL SOLUTIONS PARTNER

# TECHNICAL DATA

# MICROPOWER ST110 PB 80V/110A BATTERY CHARGERS

## STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|---|---|
| Family | ST110 |
| DC Rating | 80V/110A |
| Part number | AV6449-B1 |
| Model code | 1AA8055 |
| Part status | Released |

## SUPPLY

| | |
|---|---|
| Number of phases | 3 |
| Rated Voltage range [V] | 380-440 |
| Nominal Voltage [V] | 400 |
| Rated frequency [Hz] | 50-60 |
| Current at nominal voltage [A] | 16.9 |
| Current at min rated voltage [A] | 17.8 |
| Current at max rated voltage [A] | 15.4 |
| Recommended supply fuse class | C |
| Recommended RCCB class | B |
| Supply cable area | 4x4 mm2 |
| Supply cable length [m] | □2.5 |
| Typical Supply Connector | CEE32 |
| Standby Power Consumption [W] | <5 |
| Power Consumption [W] | 11121 |
| Apparent Power Consumption [VA] | 11706 |
| Power Factor | 0.95 |
| Leakage current [mA] | <3.5 |
| Efficiency (at rated power and no cables) [%] | 96 |

## OUTPUT DATA

| | |
|---|---|
| Reversed polarity protection | Fuse |
| Short Circuit Protection | Yes |
| Output Voltage [V] | 80 |
| Output Current [A] | 110 |
| Output cable cross-section | 35 mm2 |
| Output cable length [m] | 3 |
| Output cable terminals (in unit) | M8 |
| Typical Output connector | DIN160 |
| Output fuse, rating [A/VDC] | 150A/150VDC |
| Output fuse type | Fast Semiconductor fuse |

## PROPERTIES

| | |
|---|---|
| Ingress protection | IP20 |
| Operation Temperature [deg C] | -5 to +40 |
| Ambient max temp (with reduced output power) [deg C] | 50 |
| Ambient storage and transport temperature [C] | -40 to +80/1000h |
| Maximum operating altitude [m] | 2000 |
| Maximum humidity, non-condensing [%] | 90 |
| Cooling | Fan |
| Cabinet Type | A19 |
| Certifications | CE |
| Cloud connection | Yes |
| User interface | LED/Display |
| Charging Curve Set | Multiple Lead |
| I/O-cards | Optional |
| Reporting | Yes |
| Radio communication | Yes |

## CHARGER DIMENSIONS

| | |
|---|---|
| Weight excl. cables [kg] | 18 |
| Charger dimensions [mm] | 571x270x258 |

## SHIPPING DIMENSIONS

| | |
|---|---|
| Box dimensions [mm] | 425x380x690 |
| Shipping Weight [kg] | 24 |

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*

Micropower Group
Gullhallavägen 20
SE-352 50 Växjö
Sweden

Phone: +46 (0) 470-72 74 00
sales@micropower.se
www.micropower-group.se