

## TECHNICAL DATA

# SHARP 100 36V/150A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

|             |           |
|-------------|-----------|
| Family      | SHARP 100 |
| DC Rating   | 36V/150A  |
| Part number | SS3523    |
| Model code  | 1AB7701   |
| Part status | Released  |

| SUPPLY                                        |                     |
|-----------------------------------------------|---------------------|
| Number of phases                              | 3                   |
| Rated Voltage range [V]                       | 208-240             |
| Nominal Voltage [V]                           | 208                 |
| Rated frequency [Hz]                          | 50-60               |
| Current at nominal voltage [A]                | 21,1                |
| Current at min rated voltage [A]              | 21,1                |
| Current at max rated voltage [A]              | 18,3                |
| Recommended supply fuse class                 | C                   |
| Recommended RCCB class                        | B                   |
| Supply cable area                             | 4x4 mm <sup>2</sup> |
| Supply cable length [m]                       | 12,5                |
| Typical Supply Connector                      | CEE32               |
| Standby Power Consumption [W]                 | <10                 |
| Power Consumption [W]                         | 7220                |
| Apparent Power Consumption [VA]               | 7600                |
| Power Factor                                  | 0,95                |
| Leakage current [mA]                          | <3,5                |
| Efficiency (at rated power and no cables) [%] | 91                  |

## OUTPUT DATA

|                                  |                         |
|----------------------------------|-------------------------|
| Reversed polarity protection     | Fuse                    |
| Short Circuit Protection         | Yes                     |
| Output Voltage [V]               | 36                      |
| Output Current [A]               | 150                     |
| Output cable cross-section       | 50 mm <sup>2</sup>      |
| Output cable length [m]          | 3                       |
| Output cable terminals (in unit) | M8                      |
| Typical Output connector         | DIN160                  |
| Output fuse, rating [A/VDC]      | 200A/150VDC             |
| Output fuse type                 | Fast Semiconductor fuse |

## PROPERTIES

|                                                      |                     |
|------------------------------------------------------|---------------------|
| Ingress protection                                   | IP20                |
| Operation Temperature [deg C]                        | -5 to +40           |
| Ambient max temp (with reduced output power) [deg C] | 50                  |
| Ambient storage and transport temperature [C]        | -40 to +80/1000h    |
| Maximum operating altitude [m]                       | 2000                |
| Maximum humidity, non-condensing [%]                 | 90                  |
| Cooling                                              | Fan                 |
| Cabinet Type                                         | S18                 |
| Certifications                                       | CE                  |
| Cloud connection                                     | No                  |
| User interface                                       | LED                 |
| Charging Curve Set                                   | 10-04,06,18 & 20-09 |
| I/O-cards                                            | No                  |
| Reporting                                            | No                  |
| Radio communication                                  | No                  |

## CHARGER DIMENSIONS

|                          |             |
|--------------------------|-------------|
| Weight excl. cables [kg] | 16          |
| Charger dimensions [mm]  | 529x256x243 |

# SHIPPING DIMENSIONS

|                      |             |
|----------------------|-------------|
| Box dimensions [mm]  | 650x370x440 |
| Shipping Weight [kg] | 23          |

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*