

## TECHNICAL DATA

# LION 200 36V/420A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	LU3886
Model	LION 200
Type	36V/420A

#### MAINS DATA (50/60HZ)

Output Voltage [V]	36.0
Output Current [A]	420.0
Number of phases	3
Rated Voltage range [V]	-
Current at nominal voltage [A]	25.3
Recommended supply fuse [A]	32.0
Supply cable area	4xAWG8
Supply cable length [m]	3
Typical Supply Connector	L16-50P
Output cable cross-section	3/0 (x2) AWG

#### BATTERY CONNECTION

Output cable cross-section	3/0 (x2) AWG
Output cable terminals (in unit)	M10
Output cable length [m]	3.0
Typical Output connector	DIN640
Output Voltage [V]	36.0

#### ELECTRIC DATA

Standby Power Consumption [W]	<15
Power Consumption [W]	19961.0
Apparent Power Consumption [VA]	21012.0

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	92.0

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50.0
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A22
Certifications	UL
HMI	LED / Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Lituim, CAN Control
I/O-cards	CAN included
CE	No
UL	Yes

## CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

## CHARGER DIMENSIONS

Weight excl. cables [kg]	35
Weight incl. cables [kg]	48
Outer Dimensions Height [mm]	659

Outer Dimensions Width [mm]	256
Outer Dimensions Depth [mm]	459
Min Spacing Required	Se User Manual

## SHIPPING DIMENSIONS

Shipping Weight [kg]	51
Box Height [mm]	435
Box Width [mm]	370
Box Depth [mm]	690

## CHARGING

Charging Ionic	0
Charging Standard	0
Charging Gel	0
Charging Li-Ion	0
Charging AGM	0
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.*