

TECHNICAL DATA

MICROPOWER SL170 PB 48V/300A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	DB4769
Model	Micropower SL170
Type	48V/300A
MAINS DATA (50/60HZ)	
Output Voltage [V]	48
Output Current [A]	300
Number of phases	3
Rated Voltage range [V]	380-440
Current at nominal voltage [A]	27,9
Recommended supply fuse [A]	32
Supply cable area	4x6 mm ²
Supply cable length [m]	> 2,5
Typical Supply Connector	CEE32
Output cable cross-section	4/0 AWG
BATTERY CONNECTION	
Output cable cross-section	4/0 AWG
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN320
Output Voltage [V]	48
ELECTRIC DATA	
Standby Power Consumption [W]	<10
Power Consumption [W]	18484
Apparent Power Consumption [VA]	19334

Power Factor	0,956
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	94,9

PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	-
Cabinet Type	B2
Certifications	CE
HMI	LED/Display
HMI Language	-
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Multiple Lead
I/O-cards	Remote Start/Stop
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]	42
Weight incl. cables [kg]	50
Outer Dimensions Height [mm]	415

Outer Dimensions Width [mm]	579
Outer Dimensions Depth [mm]	520
Min Spacing Required	See User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	64
Box Height [mm]	560
Box Width [mm]	800
Box Depth [mm]	600

CHARGING

Charging Ionic

Charging Standard

Charging Gel

Charging Li-Ion

Charging AGM

Moisture Resistance No

Dusty Environment No

Outdoor use No

Cold store No

Tropical No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.