

TECHNICAL DATA

ACCESS 50 24V/100A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	AP2423
Model	ACCESS 50
Type	24V/100A

MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	100
Number of phases	3
Rated Voltage range [V]	200-240
Current at nominal voltage [A]	9.8
Recommended supply fuse [A]	10
Supply cable area	4x1,5 mm ²
Supply cable length [m]	3
Typical Supply Connector	CEE16
Output cable cross-section	35 mm ²

BATTERY CONNECTION

Output cable cross-section	35 mm ²
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN160
Output Voltage [V]	24

ELECTRIC DATA

Standby Power Consumption [W]	< 5
Power Consumption [W]	3220
Apparent Power Consumption [VA]	3389

Power Factor	0.95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	91

PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A16
Certifications	CE
HMI	LED/Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Multiple
I/O-cards	Optional
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h	574
8 Hours cap.ah/5h	833
10 Hours cap.ah/5h	1112
12 Hours cap.ah/5h	1532

CHARGER DIMENSIONS

Weight excl. cables [kg]	7
Weight incl. cables [kg]	10
Outer Dimensions Height [mm]	387

Outer Dimensions Width [mm]	266
Outer Dimensions Depth [mm]	152
Min Spacing Required	Se User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	11
Box Height [mm]	260
Box Width [mm]	325
Box Depth [mm]	550

CHARGING

Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-Ion	0
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.