

TECHNICAL DATA

ACCESS 50 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	AP3343
Model	ACCESS 50
Туре	36V/60A
MAINS DATA (50/60HZ)	
Output Voltage [V]	36
Output Current [A]	60
Number of phases	3
Rated Voltage range [V]	200-240
Current at nominal voltage [A]	8,4
Recommended supply fuse [A]	10
Supply cable area	4x1,5
Supply cable length [m]	3
Typical Supply Connector	Not included
Output cable cross-section	2x16
BATTERY CONNECTION	
Output cable cross-section	2x16
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	User defined
Output Voltage [V]	36
ELECTRIC DATA	
Standby Power Consumption [W]	< 5
Power Consumption [W]	2888
Apparent Power Consumption [VA]	3040

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	Negligible
Output Ripple	<1
Efficiency (at rated power and no cables) [%]	91
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Fan
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	A16
Certifications	
НМІ	LED/Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Multiple
I/O-cards	Optional
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	344
8 Hours cap.ah/5h	500
10 Hours cap.ah/5h	667
12 Hours cap.ah/5h	919
CHARGER DIMENSIONS	
Weight excl. cables [kg]	
Weight incl. cables [kg]	
Outer Dimensions Height [mm]	387

Outer Dimensions Width [mm]	266
Outer Dimensions Depth [mm]	152
Min Spacing Required	100
SHIPPING DIMENSIONS	
Shipping Weight [kg]	9
Box Height [mm]	260
Box Width [mm]	330
Box Depth [mm]	550
CHARGING	
Charging Ionic	LK10-18 Ionic mixture
Charging Ionic Charging Standard	LK10-18 Ionic mixture LK10-06 Standard Curve
Charging Standard	LK10-06 Standard Curve
Charging Standard Charging Gel	LK10-06 Standard Curve LK20-09
Charging Standard Charging Gel Charging Li-Ion	LK10-06 Standard Curve LK20-09 O
Charging Standard Charging Gel Charging Li-Ion Charging AGM	LK10-06 Standard Curve LK20-09 0 LK20-09
Charging Standard Charging Gel Charging Li-Ion Charging AGM Moisture Resistance	LK10-06 Standard Curve LK20-09 0 LK20-09 No
Charging Standard Charging Gel Charging Li-Ion Charging AGM Moisture Resistance Dusty Environment	LK10-06 Standard Curve LK20-09 0 LK20-09 No No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.