

# TECHNICAL DATA

## LION 130 80V/130A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	LX6489
Model	LION 130
Type	80V/130A

### MAINS DATA (50/60HZ)

Output Voltage [V]	80
Output Current [A]	130
Number of phases	3
Rated Voltage range [V]	380-440
Current at nominal voltage [A]	20,1
Recommended supply fuse [A]	25
Supply cable area	4x4 mm <sup>2</sup>
Supply cable length [m]	2,5
Typical Supply Connector	CEE32
Output cable cross-section	50 mm <sup>2</sup>

### BATTERY CONNECTION

Output cable cross-section	50 mm <sup>2</sup>
Output cable terminals (in unit)	M8
Output cable length [m]	3
Typical Output connector	DIN160
Output Voltage [V]	80

### ELECTRIC DATA

Standby Power Consumption [W]	<5
Power Consumption [W]	13208
Apparent Power Consumption [VA]	13903

Power Factor	0,95
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	95

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A19
Certifications	CE
HMI	LED/Display
HMI Language	SV / EN / DE / ES / PT
Reporting	Yes
Radio Communication	No
Charging Curve Set	N/A
I/O-cards	Optional
CE	Yes
UL	No

## CHARGING TIMES

6 Hours cap.ah/5h
8 Hours cap.ah/5h
10 Hours cap.ah/5h
12 Hours cap.ah/5h

## CHARGER DIMENSIONS

Weight excl. cables [kg]	18
Weight incl. cables [kg]	22
Outer Dimensions Height [mm]	571

Outer Dimensions Width [mm]	270
Outer Dimensions Depth [mm]	258
Min Spacing Required	See User Manual

## SHIPPING DIMENSIONS

Shipping Weight [kg]	25
Box Height [mm]	425
Box Width [mm]	380
Box Depth [mm]	690

## CHARGING

Charging Ionic	0
Charging Standard	0
Charging Gel	0
Charging Li-Ion	0
Charging AGM	0
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.