

## TECHNICAL DATA

# LION 30 24V/100A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	LION 30
DC Rating	24V/100A
Part number	LC2420
Model code	3A84001
Part status	Released

### SUPPLY

Number of phases	1
Rated Voltage range [V]	220-240
Nominal Voltage [V]	230
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	13,9
Current at min rated voltage [A]	14,6
Current at max rated voltage [A]	13,4
Recommended supply fuse class	C
Recommended RCCB class	A
Supply cable area	3x1,5 mm <sup>2</sup>
Supply cable length [m]	2,5
Typical Supply Connector	CEE17
Standby Power Consumption [W]	<5
Power Consumption [W]	3172
Apparent Power Consumption [VA]	3204
Power Factor	0,99
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	93

## OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	24
Output Current [A]	100
Output cable cross-section	25 mm <sup>2</sup>
Output cable length [m]	3
Output cable terminals (in unit)	M6
Typical Output connector	DIN160
Output fuse, rating [A/VDC]	150A/150VDC
Output fuse type	Inline external, Fast Semiconductor fuse

## PROPERTIES

Ingress protection	IP54 (IP66 optional)
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A12
Certifications	CE
Cloud connection	No
User interface	LED
Charging Curve Set	Litium Alg or CAN
I/O-cards	CAN/Detect
Reporting	No
Radio communication	Yes

## CHARGER DIMENSIONS

Weight excl. cables [kg]	7
Charger dimensions [mm]	408x235x78

## SHIPPING DIMENSIONS

Box dimensions [mm]	165x265x600
Shipping Weight [kg]	11

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*