

## **TECHNICAL DATA**

## SHARP 100 80V/80A BATTERY CHARGERS

## STATED DATA ACCORDING TO MICROPOWER STANDARD

| Part number                      | SS6383    |
|----------------------------------|-----------|
| Model                            | SHARP 100 |
| Туре                             | 80V/80A   |
| MAINS DATA (50/60HZ)             |           |
| Output Voltage [V]               | 80        |
| Output Current [A]               | 80        |
| Number of phases                 | 3         |
| Rated Voltage range [V]          | 208-240   |
| Current at nominal voltage [A]   | 24.3      |
| Recommended supply fuse [A]      | 25        |
| Supply cable area                | 4x4 mm2   |
| Supply cable length [m]          | 3         |
| Typical Supply Connector         | CEE32     |
| Output cable cross-section       | 25 mm2    |
| BATTERY CONNECTION               |           |
| Output cable cross-section       | 25 mm2    |
| Output cable terminals (in unit) | M8        |
| Output cable length [m]          | 3         |
| Typical Output connector         | DIN80     |
| Output Voltage [V]               | 80        |
| ELECTRIC DATA                    |           |
| Standby Power Consumption [W]    | <10       |
| Power Consumption [W]            | 8306      |
| Apparent Power Consumption [VA]  | 8743      |

| Power Factor   | 0.95                |
|--|---------------------|
| Inrush current, do not tripp fuse of class [A]           | В                   |
| Output Ripple  | <5                  |
| Efficiency (at rated power and no cables) [%]            | 93                  |
| PROPERTIES   |                     |
| Ingress protection                                       | IP20                |
| Ambient temperature range (at full output power) [deg C] | -5 to +40           |
| Ambient max temp (with reduced output power) [deg C]     | 50                  |
| Cooling  | Convection          |
| Short Circuit Protection                                 | Yes                 |
| Wrong Polarity Protection                                | Fuse                |
| Cabinet Type   | S18                 |
| Certifications   | CE                  |
| НМІ  | LED                 |
| HMI Language   | -                   |
| Reporting  | No                  |
| Radio Communication                                      | No                  |
| Charging Curve Set                                       | 10-04,06,18 & 20-09 |
| I/O-cards  | No                  |
| CE   | Yes                 |
| UL   | No                  |
| CHARGING TIMES   |                     |
| 6 Hours cap.ah/5h  | 459                 |
| 8 Hours cap.ah/5h  | 665                 |
| 10 Hours cap.ah/5h                                       | 887                 |
| 12 Hours cap.ah/5h                                       | 1064                |
| CHARGER DIMENSIONS                                       |                     |
| Weight excl. cables [kg]                                 | 16                  |
| Weight incl. cables [kg]                                 | 19                  |
| Outer Dimensions Height [mm]                             | 529                 |
|  |                     |

| Outer Dimensions Width [mm]   | 256                                 |
|---|-------------------------------------|
| Outer Dimensions Depth [mm]   | 243                                 |
| Min Spacing Required  | Se User Manual                      |
| SHIPPING DIMENSIONS   |                                     |
| Shipping Weight [kg]  | 22                                  |
| Box Height [mm]   | 650                                 |
| Box Width [mm]  | 370                                 |
| Box Depth [mm]  | 440                                 |
| CHARGING  |                                     |
| Charging Ionic  | LK10-18 Ionic mixture               |
|   |                                     |
| Charging Standard   | LK10-06 Standard Curve              |
| Charging Standard<br>Charging Gel   | LK10-06 Standard Curve<br>LK20-09   |
|   |                                     |
| Charging Gel  | LK20-09                             |
| Charging Gel<br>Charging Li-Ion   | LK20-09<br>0                        |
| Charging Gel Charging Li-Ion Charging AGM   | LK20-09<br>0<br>LK20-09             |
| Charging Gel         Charging Li-Ion         Charging AGM         Moisture Resistance                           | LK20-09<br>0<br>LK20-09<br>No       |
| Charging Gel         Charging Li-Ion         Charging AGM         Moisture Resistance         Dusty Environment | LK20-09<br>0<br>LK20-09<br>No<br>No |

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.