

TECHNICAL DATA

MICROPOWER SQ60 PB 24V/200A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	SQ60
DC Rating	24V/200A
Part number	SN2629
Model code	1AB645A
Part status	Released

SUPPLY

Number of phases	3
Rated Voltage range [V]	380-440
Nominal Voltage [V]	400
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	9,6
Current at min rated voltage [A]	10,1
Current at max rated voltage [A]	8,7
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4x1,5 mm ²
Supply cable length [m]	12,5
Typical Supply Connector	CEE16
Standby Power Consumption [W]	<2,5
Power Consumption [W]	6302
Apparent Power Consumption [VA]	6655
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	93

OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	24
Output Current [A]	200
Output cable cross-section	70 mm ²
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN320
Output fuse, rating [A/VDC]	250A/150VDC
Output fuse type	Fast Semiconductor fuse

PROPERTIES

Ingress protection	IP21
Operation Temperature [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%]	90
Cooling	Convection
Cabinet Type	A24
Certifications	CE
Cloud connection	No
User interface	LED
Charging Curve Set	10-04,06,18 & 20-09
I/O-cards	Optional
Reporting	No
Radio communication	No

CHARGER DIMENSIONS

Weight excl. cables [kg]	8
Charger dimensions [mm]	338x335x239

SHIPPING DIMENSIONS

Box dimensions [mm]	350x380x530
Shipping Weight [kg]	16

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.