

TECHNICAL DATA

MICROPOWER SL450 LI 120V/310A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	SL450
DC Rating	120V/310A
Part number	ED7776-B3/A
Model code	1A6B4AP
Part status	Released

SUPPLY

Number of phases	3
Rated Voltage range [V]	480
Nominal Voltage [V]	480
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	58,6
Current at min rated voltage [A]	58,6
Current at max rated voltage [A]	58,6
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4xAWG4
Supply cable length [m]	12,5
Typical Supply Connector	P&S 100A
Standby Power Consumption [W]	<3,5
Power Consumption [W]	46605
Apparent Power Consumption [VA]	48699
Power Factor	0,96
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	96

OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	120
Output Current [A]	310
Output cable cross-section	2/0(x2) AWG
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	2xDIN320
Output fuse, rating [A/VDC]	4x125A/150VDC
Output fuse type	Fast Semiconductor fuse

PROPERTIES

Ingress protection	IP21
Operation Temperature [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%]	90
Cooling	Convection
Cabinet Type	B4
Certifications	UL
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Litium Alg or CAN
I/O-cards	CAN/Detect
Reporting	Yes
Radio communication	Yes

CHARGER DIMENSIONS

Weight excl. cables [kg]	76
Charger dimensions [mm]	415x579x520

SHIPPING DIMENSIONS

Box dimensions [mm]	560x800x600
Shipping Weight [kg]	105

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.