

TECHNICAL DATA

SHARP 30 48V/60A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	Sharp 30
DC Rating	48V/60A
Part number	SC4340
Model code	3A94005
Part status	Released

SUPPLY

Number of phases	1
Rated Voltage range [V]	220-240
Nominal Voltage [V]	230
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	15
Current at min rated voltage [A]	15
Current at max rated voltage [A]	15
Recommended supply fuse class	C
Recommended RCCB class	A
Supply cable area	3x1,5 mm ²
Supply cable length [m]	2,5
Typical Supply Connector	CEE17
Standby Power Consumption [W]	<5
Power Consumption [W]	3409
Apparent Power Consumption [VA]	3444
Power Factor	0,99
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	93

OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	48
Output Current [A]	60
Output cable cross-section	16 mm ²
Output cable length [m]	3
Output cable terminals (in unit)	M6
Typical Output connector	DIN80
Output fuse, rating [A/VDC]	80A/150VDC
Output fuse type	Inline external, Fast Semiconductor fuse

PROPERTIES

Ingress protection	IP54 (IP66 optional)
Operation Temperature [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%]	90
Cooling	Fan
Cabinet Type	S12
Certifications	CE
Cloud connection	No
User interface	LED
Charging Curve Set	10-04,06,18 & 20-09
I/O-cards	No
Reporting	No
Radio communication	No

CHARGER DIMENSIONS

Weight excl. cables [kg]	7
Charger dimensions [mm]	408x235x78

SHIPPING DIMENSIONS

Box dimensions [mm]	165x265x600
---------------------	-------------

Shipping Weight [kg]	10
----------------------	----

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.