

TECHNICAL DATA

LION 200 80V/200A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

| | |
|-------------|----------|
| Family | LION 200 |
| DC Rating | 80V/200A |
| Part number | LU6624 |
| Model code | 1AA8522 |
| Part status | Released |

SUPPLY

| | |
|---|---------------------|
| Number of phases | 3 |
| Rated Voltage range [V] | 440-440 |
| Nominal Voltage [V] | 440 |
| Rated frequency [Hz] | 50-60 |
| Current at nominal voltage [A] | 28,4 |
| Current at min rated voltage [A] | 28,4 |
| Current at max rated voltage [A] | 28,4 |
| Recommended supply fuse class | C |
| Recommended RCCB class | B |
| Supply cable area | 4x6 mm ² |
| Supply cable length [m] | 2,5 |
| Typical Supply Connector | CEE32 |
| Standby Power Consumption [W] | <15 |
| Power Consumption [W] | 20553 |
| Apparent Power Consumption [VA] | 21635 |
| Power Factor | 0,95 |
| Leakage current [mA] | <3,5 |
| Efficiency (at rated power and no cables) [%] | 94 |

OUTPUT DATA

| | |
|----------------------------------|-------------------------|
| Reversed polarity protection | Fuse |
| Short Circuit Protection | Yes |
| Output Voltage [V] | 80 |
| Output Current [A] | 200 |
| Output cable cross-section | 70 mm ² |
| Output cable length [m] | 3 |
| Output cable terminals (in unit) | M10 |
| Typical Output connector | DIN320 |
| Output fuse, rating [A/VDC] | 2x150A/150VDC |
| Output fuse type | Fast Semiconductor fuse |

PROPERTIES

| | |
|--|-------------------|
| Ingress protection | IP20 |
| Ambient temperature range (at full output power) [deg C] | -5 to +40 |
| Ambient max temp (with reduced output power) [deg C] | 50 |
| Ambient storage and transport temperature [C] | -40 to +80/1000h |
| Maximum operating altitude [m] | 2000 |
| Maximum humidity, non-condensing [%rh] | 90 |
| Cooling | Convection |
| Cabinet Type | A22 |
| Certifications | CE |
| Cloud connection | Yes |
| User interface | LED/Display |
| Charging Curve Set | Litium Alg or CAN |
| I/O-cards | CAN/Detect |
| Reporting | Yes |
| Radio communication | Yes |

CHARGER DIMENSIONS

| | |
|--------------------------|-------------|
| Weight excl. cables [kg] | 34 |
| Charger dimensions [mm] | 659x256x459 |

SHIPPING DIMENSIONS

Box dimensions [mm]

435x370x690

Shipping Weight [kg]

45

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.