

TECHNICAL DATA

SHARP 11 24V/40A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER	R STANDARD
Part number	\$12306
Model	SHARP 11
Туре	24V/40A
MAINS DATA (50/60HZ)	
Output Voltage [V]	24
Output Current [A]	40
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	5,5
Recommended supply fuse [A]	10
Supply cable area	3x1,0mm2
Supply cable length [m]	2,3
Typical Supply Connector	10A Schuko
Output cable cross-section	10 mm2
BATTERY CONNECTION	
Output cable cross-section	10 mm2
Output cable terminals (in unit)	M5
Output cable length [m]	2
Typical Output connector	User defined
Output Voltage [V]	24
ELECTRIC DATA	
Standby Power Consumption [W]	<5
Power Consumption [W]	1307
Apparent Power Consumption [VA]	1320

Printout date: 2025-08-22

Power Factor	0,99
Inrush current, do not tripp fuse of class [A]	В
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	92
PROPERTIES	
Ingress protection	IP66
Ambient temperature range (at full output power) [deg C]	-35 to +40
Ambient max temp (with reduced output power) [deg C]	55
Cooling	Convection
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	S40
Certifications	CE
HMI	LED
HMI Language	-
Reporting	No
Radio Communication	No
Charging Curve Set	N/A
I/O-cards	Optional
CE	Yes
UL	No
CHARGING TIMES	
6 Hours cap.ah/5h	235
8 Hours cap.ah/5h	340
10 Hours cap.ah/5h	445
12 Hours cap.ah/5h	550
CHARGER DIMENSIONS	
Weight excl. cables [kg]	3.2
Weight incl. cables [kg]	3.9

Outer Dimensions Width [mm]	230
Outer Dimensions Depth [mm]	80
Min Spacing Required	See User Manual
SHIPPING DIMENSIONS	
Shipping Weight [kg]	4.5
Box Height [mm]	135
Box Width [mm]	380
Box Depth [mm]	250
CHARGING	
Charging Ionic	LK10-18 Ionic mixture
Charging Standard	LK10-06 Standard Curve
Charging Gel	LK20-09
Charging Li-lon	YES
Charging AGM	LK20-09
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No