MICROPOWER GROUP™
POWERFUL SOLUTIONS PARTNER

TECHNICAL DATA

LION 11 24V/35A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	L12291
Model	Lion 11
Type	24V/35A
MAINS DATA (50/60HZ)	
Output Voltage [V]	24
Output Current [A]	35
Mains Phase	1
Input Voltage [V]	100-240
Max Mains Current (at nominal mains V) [A]	4,2
Recommended Mains Fuse [A]	10
Mains Cable Area [mm2]	3x1,0 mm2
Mains Cable Length [m]	2,3
Mains Connector	10A Schuko
Battery Cable [mm2]	10 mm2
BATTERY CONNECTION	
Battery Cable [mm2]	10 mm2
Battery Cable Connection (in charger)	M5
Battery Cable Length [m]	2
Battery Connector (not included)	User defined
Output Voltage [V]	24
ELECTRIC DATA	
Standby Power Consumption [W]	<5
Power Consumption [W]	990
Apparent Power Consumption [VA]	1000

Power Factor	0,99
Inrush Current [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	92

PROPERTIES

IP Protection	IP20
Operation Temperature [deg C]	-35 to +40
Ambient Max Temperature (with reduced capacity) [deg C]	55
Cooling	Convection
Short Circuit Protection	1
Wrong Polarity Protection	Fuse
Cabinet Type	S40
Certifications	CE
HMI	LED
HMI Language	-
Bluetooth/ NFC connectivity	No
Remote connectivity & advanced software functions	No
Charging Curve Set	N/A
I/O-cards	Optional
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h
8 Hours cap.ah/5h
10 Hours cap.ah/5h
12 Hours cap.ah/5h

CHARGER DIMENSIONS

Charger Weight excl. Cables [kg]	3.2
Charger Weight incl. Cables [kg]	3.9
Outer Dimensions Height [mm]	262

Outer Dimensions Width [mm]	230
Outer Dimensions Depth [mm]	80
Min Spacing Required	See User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	4.5
Box Height [mm]	135
Box Width [mm]	380
Box Depth [mm]	250

CHARGING

Charging Ionic	
Charging Standard	
Charging Gel	
Charging Li-Ion	CAN bus, external BMS
Charging AGM	
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.

Micropower Group
Gulhallavägen 20
SE-352 50 Växjö
Sweden

Phone: +46 (0) 470-72 74 00
sales@micropower.se
www.micropower-group.se