

TECHNICAL DATA

MICROPOWER SX14 PB 24V/50A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	WG2320-A1
Model	SX14
Type	24V/50A

MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	50
Number of phases	1
Rated Voltage range [V]	220-240
Current at nominal voltage [A]	7.2
Recommended supply fuse [A]	10
Supply cable area	3x1.5 mm ²
Supply cable length [m]	2.3
Typical Supply Connector	Fixed or IEC C19/CEE17
Output cable cross-section	16 mm ²

BATTERY CONNECTION

Output cable cross-section	16 mm ²
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	24

ELECTRIC DATA

Standby Power Consumption [W]	<5
Power Consumption [W]	1612,637363
Apparent Power Consumption [VA]	1645,548329

Power Factor	0.98
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	91

PROPERTIES

Ingress protection	IP21
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	55
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	Fuse
Cabinet Type	A51
Certifications	CE
HMI	LED/Display
HMI Language	SV / EN / ES / PT / DE
Reporting	Yes
Radio Communication	Yes
Charging Curve Set	Multiple Lead
I/O-cards	Basic
CE	Yes
UL	No

CHARGING TIMES

6 Hours cap.ah/5h	255
8 Hours cap.ah/5h	383
10 Hours cap.ah/5h	523
12 Hours cap.ah/5h	605

CHARGER DIMENSIONS

Weight excl. cables [kg]	6.1
Weight incl. cables [kg]	7.6
Outer Dimensions Height [mm]	455

Outer Dimensions Width [mm]	220
Outer Dimensions Depth [mm]	103
Min Spacing Required	See User Manual

SHIPPING DIMENSIONS

Shipping Weight [kg]	9.2
Box Height [mm]	165
Box Width [mm]	265
Box Depth [mm]	595

CHARGING

Charging Ionic	LK-10-04
Charging Standard	
Charging Gel	
Charging Li-Ion	
Charging AGM	
Moisture Resistance	No
Dusty Environment	No
Outdoor use	No
Cold store	No
Tropical	No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.