

## TECHNICAL DATA

# MICROPOWER SX14 PB 24V/50A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	WG2321
Model	Micropower SX14
Type	24V/50A

#### MAINS DATA (50/60HZ)

Output Voltage [V]	24
Output Current [A]	50
Number of phases	1
Rated Voltage range [V]	120-240
Current at nominal voltage [A]	7,2
Recommended supply fuse [A]	10A @220-240V / 16A @120V
Supply cable area	3xAWG12
Supply cable length [m]	2,3
Typical Supply Connector	Fixed or IEC / NEMA 6-20P
Output cable cross-section	16 mm <sup>2</sup>

#### BATTERY CONNECTION

Output cable cross-section	16 mm <sup>2</sup>
Output cable terminals (in unit)	M6
Output cable length [m]	3
Typical Output connector	DIN80
Output Voltage [V]	24

#### ELECTRIC DATA

Standby Power Consumption [W]	<5
Power Consumption [W]	1613
Apparent Power Consumption [VA]	1646

Power Factor	0,98
Inrush current, do not tripp fuse of class [A]	B
Output Ripple	<5
Efficiency (at rated power and no cables) [%]	91

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	55
Cooling	Convection
Short Circuit Protection	Yes
Wrong Polarity Protection	
Cabinet Type	A51
Certifications	UL
HMI	
HMI Language	
Reporting	No
Radio Communication	No
Charging Curve Set	
I/O-cards	
CE	No
UL	Yes

## CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

## CHARGER DIMENSIONS

Weight excl. cables [kg]	6
Weight incl. cables [kg]	8
Outer Dimensions Height [mm]	455

Outer Dimensions Width [mm]	220
-----------------------------	-----

Outer Dimensions Depth [mm]	103
-----------------------------	-----

Min Spacing Required	See User Manual
----------------------	-----------------

## SHIPPING DIMENSIONS

Shipping Weight [kg]	9
----------------------	---

Box Height [mm]	165
-----------------	-----

Box Width [mm]	265
----------------	-----

Box Depth [mm]	595
----------------	-----

## CHARGING

Charging Ionic	
----------------	--

Charging Standard	
-------------------	--

Charging Gel	
--------------	--

Charging Li-Ion	
-----------------	--

Charging AGM	
--------------	--

Moisture Resistance	No
---------------------	----

Dusty Environment	No
-------------------	----

Outdoor use	No
-------------	----

Cold store	No
------------	----

Tropical	No
----------	----

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower E.D. Marketing AB.*