MICROPOWER GROUP™
POWERFUL SOLUTIONS PARTNER

TECHNICAL DATA

MIL DC-DC CONVERTER ISOLATED DC-DC CONVERTERS & CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number	0060323MIL
Model	MIL DC-DC Converter
Type	48V/24V 400W

MAINS DATA (50/60HZ)

Output Voltage [V]	28
Output Current [A]	
Mains Phase	
Input Voltage [V]	
Max Mains Current (at nominal mains V) [A]	
Recommended Mains Fuse [A]	
Mains Cable Area [mm2]	
Mains Cable Length [m]	
Mains Connector	
Battery Cable [mm2]	

BATTERY CONNECTION

Battery Cable [mm2]	
Battery Cable Connection (in charger)	
Battery Cable Length [m]	
Battery Connector (not included)	
Output Voltage [V]	28

PROPERTIES

IP Protection	IP67
Operation Temperature [deg C]	

Ambient Max Temperature (with reduced capacity) [deg C]
Cooling
Short Circuit Protection
Wrong Polarity Protection
Cabinet Type
Certifications
HMI
HMI Language
Bluetooth/ NFC connectivity
Remote connectivity & advanced software functions
Charging Curve Set
I/O-cards
CE
UL

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.

Micropower Group
Gulhallavägen 20
SE-352 50 Växjö
Sweden

Phone: +46 (0) 470-72 74 00
sales@micropower.se
www.micropower-group.se