

TECHNICAL DATA

PAC/PAP 750UL 750W 12/40 BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD

Part number

Model

PAC/PAP 750UL 750W

Type

12V/40A Fan Cooling

MAINS DATA (50/60HZ)

Output Voltage [V]

12

Output Current [A]

40

Number of phases

Rated Voltage range [V]

55-250

Current at nominal voltage [A]

Recommended supply fuse [A]

Supply cable area

Supply cable length [m]

Typical Supply Connector

Output cable cross-section

BATTERY CONNECTION

Output cable cross-section

Output cable terminals (in unit)

Output cable length [m]

Typical Output connector

Output Voltage [V]

12

ELECTRIC DATA

Standby Power Consumption [W]

Power Consumption [W]

Apparent Power Consumption [VA]

Power Factor

Inrush current, do not tripp fuse of class [A]

Output Ripple

Efficiency (at rated power and no cables) [%]

PROPERTIES

Ingress protectionIP20

Ambient temperature range (at full output power) [deg C]

Ambient max temp (with reduced output power) [deg C]

Cooling

Short Circuit Protection

Wrong Polarity Protection

Cabinet Type

Certifications

HMI

HMI Language

ReportingNo

Radio CommunicationNo

Charging Curve Set

I/O-cards

CENo

ULNo

CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

CHARGER DIMENSIONS

Weight excl. cables [kg]

Weight incl. cables [kg]

Outer Dimensions Height [mm]

Outer Dimensions Width [mm]

Outer Dimensions Depth [mm]

Min Spacing Required

SHIPPING DIMENSIONS

Shipping Weight [kg]

Box Height [mm]

Box Width [mm]

Box Depth [mm]

CHARGING

Charging Ionic

Charging Standard

Charging Gel

Charging Li-Ion

Charging AGM

Moisture Resistance No

Dusty Environment No

Outdoor use No

Cold store No

Tropical No

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.