

## TECHNICAL DATA

# ECOPOINT 24V/120A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

|             |            |
|-------------|------------|
| Part number | 24V/120A-3 |
| Model       | Ecopoint   |
| Type        | 24V/120A   |

### MAINS DATA (50/60HZ)

|                                |                   |
|--------------------------------|-------------------|
| Output Voltage [V]             | 24                |
| Output Current [A]             | 120               |
| Number of phases               | 3                 |
| Rated Voltage range [V]        | 720-839           |
| Current at nominal voltage [A] | 12.1/10.5/5.3/4.2 |
| Recommended supply fuse [A]    |                   |
| Supply cable area              |                   |
| Supply cable length [m]        |                   |
| Typical Supply Connector       |                   |
| Output cable cross-section     |                   |

### BATTERY CONNECTION

|                                  |    |
|----------------------------------|----|
| Output cable cross-section       |    |
| Output cable terminals (in unit) |    |
| Output cable length [m]          |    |
| Typical Output connector         |    |
| Output Voltage [V]               | 24 |

### ELECTRIC DATA

|                                 |  |
|---------------------------------|--|
| Standby Power Consumption [W]   |  |
| Power Consumption [W]           |  |
| Apparent Power Consumption [VA] |  |

Power Factor

Inrush current, do not tripp fuse of class [A]

Output Ripple

Efficiency (at rated power and no cables) [%]

## PROPERTIES

Ingress protection

Ambient temperature range (at full output power) [deg C]

Ambient max temp (with reduced output power) [deg C]

Cooling

Short Circuit Protection

Wrong Polarity Protection

Cabinet Type

Certifications

HMI

HMI Language

Reporting No

Radio Communication No

Charging Curve Set

I/O-cards

CE No

UL No

## CHARGING TIMES

6 Hours cap.ah/5h

8 Hours cap.ah/5h

10 Hours cap.ah/5h

12 Hours cap.ah/5h

## CHARGER DIMENSIONS

Weight excl. cables [kg]

Weight incl. cables [kg]

Outer Dimensions Height [mm]

Outer Dimensions Width [mm]

Outer Dimensions Depth [mm]

Min Spacing Required

SHIPPING DIMENSIONS

Shipping Weight [kg]77.1107

Box Height [mm]

Box Width [mm]

Box Depth [mm]

CHARGING

Charging Ionic

Charging Standard

Charging Gel

Charging Li-Ion

Charging AGM

Moisture ResistanceNo

Dusty EnvironmentNo

Outdoor useNo

Cold storeNo

TropicalNo

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Group AB.