

## **TECHNICAL DATA**

## ACCESS 50 24V/100A BATTERY CHARGERS

STATED DATA ACCORDING TO MICROPOWER STANDARD	
Family	ACCESS 50
DC Rating	24V/100A
Part number	AP2426
Model code	1AA6002
Part status	Released
SUPPLY	
Number of phases	3
Rated Voltage range [V]	480
Nominal Voltage [V]	480
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	4
Current at min rated voltage [A]	4
Current at max rated voltage [A]	4
Recommended supply fuse class	С
Recommended RCCB class	В
Supply cable area	4xAWG14
Supply cable length [m]	?2,5
Typical Supply Connector	L16-20P
Standby Power Consumption [W]	<5
Power Consumption [W]	3191
Apparent Power Consumption [VA]	3359
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	92

Printout date: 2025-11-05

OUTPUT DATA	
Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	24
Output Current [A]	100
Output cable cross-section	#2 AWG
Output cable length [m]	3
Output cable terminals (in unit)	M6
Typical Output connector	DIN160
Output fuse, rating [A/VDC]	150A/150VDC
Output fuse type	Fast Semiconductor fuse
PROPERTIES	
Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A16
Certifications	UL
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Multiple Lead
1/0-cards	Optional
Reporting	Yes
Radio communication	Yes
CHARGER DIMENSIONS	
Weight excl. cables [kg]	6

## SHIPPING DIMENSIONS Box dimensions [mm] 260x325x550 Shipping Weight [kg] 11