

## TECHNICAL DATA

# LION 130 48V/220A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

Family	LION 130
DC Rating	48V/220A
Part number	LX4666
Model code	1AA7904
Part status	Released

### SUPPLY

Number of phases	3
Rated Voltage range [V]	460-480
Nominal Voltage [V]	480
Rated frequency [Hz]	50-60
Current at nominal voltage [A]	17,3
Current at min rated voltage [A]	18
Current at max rated voltage [A]	17,3
Recommended supply fuse class	C
Recommended RCCB class	B
Supply cable area	4xAWG10
Supply cable length [m]	□2.5
Typical Supply Connector	L16-30P
Standby Power Consumption [W]	<5
Power Consumption [W]	13640
Apparent Power Consumption [VA]	14328
Power Factor	0,95
Leakage current [mA]	<3,5
Efficiency (at rated power and no cables) [%]	94

## OUTPUT DATA

Reversed polarity protection	Fuse
Short Circuit Protection	Yes
Output Voltage [V]	48
Output Current [A]	220
Output cable cross-section	2/0 AWG
Output cable length [m]	3
Output cable terminals (in unit)	M8
Typical Output connector	DIN320
Output fuse, rating [A/VDC]	300A/150VDC
Output fuse type	Fast Semiconductor fuse

## PROPERTIES

Ingress protection	IP20
Ambient temperature range (at full output power) [deg C]	-5 to +40
Ambient max temp (with reduced output power) [deg C]	50
Ambient storage and transport temperature [C]	-40 to +80/1000h
Maximum operating altitude [m]	2000
Maximum humidity, non-condensing [%rh]	90
Cooling	Convection
Cabinet Type	A19
Certifications	UL
Cloud connection	Yes
User interface	LED/Display
Charging Curve Set	Litium Alg or CAN
I/O-cards	CAN/Detect
Reporting	Yes
Radio communication	Yes

## CHARGER DIMENSIONS

Weight excl. cables [kg]	18
Charger dimensions [mm]	571x270x258

## SHIPPING DIMENSIONS

Box dimensions [mm]	425x380x690
Shipping Weight [kg]	28

*The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.*