

# TECHNICAL DATA

## SHARP 80 36V/130A BATTERY CHARGERS

### STATED DATA ACCORDING TO MICROPOWER STANDARD

|             |          |
|-------------|----------|
| Family      | SHARP 80 |
| DC Rating   | 36V/130A |
| Part number | SM3489   |
| Model code  | 1AB6010  |
| Part status | Released |

### SUPPLY

|                                               |           |
|-----------------------------------------------|-----------|
| Number of phases                              | 3         |
| Rated Voltage range [V]                       | 380-440   |
| Nominal Voltage [V]                           | 400       |
| Rated frequency [Hz]                          | 50-60     |
| Current at nominal voltage [A]                | 9,4       |
| Current at min rated voltage [A]              | 9,9       |
| Current at max rated voltage [A]              | 8,5       |
| Recommended supply fuse class                 | C         |
| Recommended RCCB class                        | B         |
| Supply cable area                             | 4x1,5 mm2 |
| Supply cable length [m]                       | 2,5       |
| Typical Supply Connector                      | CEE16     |
| Standby Power Consumption [W]                 | <5        |
| Power Consumption [W]                         | 6178      |
| Apparent Power Consumption [VA]               | 6503      |
| Power Factor                                  | 0,95      |
| Leakage current [mA]                          | <3,5      |
| Efficiency (at rated power and no cables) [%] | 92        |

## OUTPUT DATA

|                                  |                         |
|----------------------------------|-------------------------|
| Reversed polarity protection     | Fuse                    |
| Short Circuit Protection         | Yes                     |
| Output Voltage [V]               | 36                      |
| Output Current [A]               | 130                     |
| Output cable cross-section       | 50 mm <sup>2</sup>      |
| Output cable length [m]          | 3                       |
| Output cable terminals (in unit) | M6                      |
| Typical Output connector         | DIN160                  |
| Output fuse, rating [A/VDC]      | 150A/150VDC             |
| Output fuse type                 | Fast Semiconductor fuse |

## PROPERTIES

|                                                          |                     |
|----------------------------------------------------------|---------------------|
| Ingress protection                                       | IP20                |
| Ambient temperature range (at full output power) [deg C] | -5 to +40           |
| Ambient max temp (with reduced output power) [deg C]     | 50                  |
| Ambient storage and transport temperature [C]            | -40 to +80/1000h    |
| Maximum operating altitude [m]                           | 2000                |
| Maximum humidity, non-condensing [%rh]                   | 90                  |
| Cooling                                                  | Convection          |
| Cabinet Type                                             | S16                 |
| Certifications                                           | CE                  |
| Cloud connection                                         | No                  |
| User interface                                           | LED                 |
| Charging Curve Set                                       | 10-04,06,18 & 20-09 |
| I/O-cards                                                | No                  |
| Reporting                                                | No                  |
| Radio communication                                      | No                  |

## CHARGER DIMENSIONS

|                          |             |
|--------------------------|-------------|
| Weight excl. cables [kg] | 6           |
| Charger dimensions [mm]  | 387x266x152 |

SHIPPING DIMENSIONS

|                      |             |
|----------------------|-------------|
| Box dimensions [mm]  | 260x325x550 |
| Shipping Weight [kg] | 12          |

The information in this document is subject to change without notice and should not be construed as a commitment by Micropower Sweden AB.