

TECHNICAL DATA

SHARP 100 36V/170A BATTERY CHARGERS

| STATED DATA ACCORDING TO MICROPOWER STANDARD | |
|----------------------------------------------|-----------|
| Part number | SS3563 |
| Model | SHARP 100 |
| Туре | 36V/170A |
| MAINS DATA (50/60HZ) | |
| Output Voltage [V] | 36 |
| Output Current [A] | 170 |
| Number of phases | 3 |
| Rated Voltage range [V] | 208-240 |
| Current at nominal voltage [A] | 23.9 |
| Recommended supply fuse [A] | 25 |
| Supply cable area | 4x4 mm2 |
| Supply cable length [m] | 3 |
| Typical Supply Connector | CEE32 |
| Output cable cross-section | 70 mm2 |
| BATTERY CONNECTION | |
| Output cable cross-section | 70 mm2 |
| Output cable terminals (in unit) | M8 |
| Output cable length [m] | 3 |
| Typical Output connector | DIN320 |
| Output Voltage [V] | 36 |
| ELECTRIC DATA | |
| Standby Power Consumption [W] | <10 |
| Power Consumption [W] | 8166 |
| Apparent Power Consumption [VA] | 8595 |

Printout date: 2025-01-30

| Inrush current, do not tripp fuse of class [A] | В |
|----------------------------------------------------------|---------------------|
| | |
| Output Ripple | <5 |
| Efficiency (at rated power and no cables) [%] | 91 |
| PROPERTIES | |
| Ingress protection | IP20 |
| Ambient temperature range (at full output power) [deg C] | -5 to +40 |
| Ambient max temp (with reduced output power) [deg C] | 50 |
| Cooling | Convection |
| Short Circuit Protection | Yes |
| Wrong Polarity Protection | Fuse |
| Cabinet Type | S18 |
| Certifications | CE |
| НМІ | LED |
| HMI Language | - |
| Reporting | No |
| Radio Communication | No |
| Charging Curve Set | 10-04,06,18 & 20-09 |
| I/O-cards | No |
| CE | Yes |
| UL | No |
| CHARGING TIMES | |
| 6 Hours cap.ah/5h | 976 |
| 8 Hours cap.ah/5h | 1415 |
| 10 Hours cap.ah/5h | 1888 |
| 12 Hours cap.ah/5h | 2266 |
| CHARGER DIMENSIONS | |
| Weight excl. cables [kg] | 16 |
| Weight incl. cables [kg] | 22 |
| Outer Dimensions Height [mm] | 529 |

| Outer Dimensions Width [mm] | 256 |
|-----------------------------|------------------------|
| Outer Dimensions Depth [mm] | 243 |
| Min Spacing Required | Se User Manual |
| SHIPPING DIMENSIONS | |
| Shipping Weight [kg] | 25 |
| Box Height [mm] | 650 |
| Box Width [mm] | 370 |
| Box Depth [mm] | 440 |
| CHARGING | |
| Charging Ionic | LK10-18 Ionic mixture |
| Charging Standard | LK10-06 Standard Curve |
| Charging Gel | LK20-09 |
| Charging Li-lon | 0 |
| Charging AGM | LK20-09 |
| Moisture Resistance | No |
| Dusty Environment | No |
| Outdoor use | No |
| Cold store | No |
| Tropical | No |